

Material Safety Data Sheet In Accordance with MOEL Public notice No 2020-130 MSDS Number: AA06900-0000000034 Issue date: 11/3/2020 Revision date: 12/29/2021 Version: 1.0

1. Chemical product and company identification		
1.1. Product identifier		
Product form Trade name	: Mixture : KST-308L	
1.2. Recommended uses and rest	rictions	
Use Categories 35 - Welding and soldering products, flux	products	
1.2.1. Recommended use Welding and soldering products, flux products.		
1.2.2. Restrictions on use		

	_		
1.3.	Supp	lier in	formation

- Supplier
Company
Address
Tel.
Fax

: KISWEL

- : (51544) South Korea 704, Gongdan-ro, Seongsan-gu, Changwon-si, Gyeongnam, Korea
- : 055)269-7200
- : 055)266-4487

2. Hazards identification

2.1. Classification of the substance or mixture

Skin corrosion/irritation, Category 1	H314
Serious eye damage/eye irritation, Category 1	H318
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity - Repeated exposure, Category 1	H372
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

2.2. Label elements

2.2.1. Hazard pictograms (GHS KR)



2.2.2. Signal word (GHS KR)

Danger.

2.2.3. Hazard statements (GHS KR)

- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H334 May cause allergic reactions, asthma or shortness of breath and etc if inhaled.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

2.2.4. Precautionary statements (GHS KR)

Precaution:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands, forearms and face thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P284 - Wear respiratory protection.

Treatment:

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 - IF ON SKIN: Wash with plenty of water/....

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER/doctor/....

P314 - Get medical advice/attention if you feel unwell.

P321 - Take ... treatment.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor/....

P362+P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

Storage:

P405 - Store locked up.

Disposal:

P501 - Dispose of contents/container according to waste related regulations.

2.3. Hazards - Other hazards which do not result in classification - Hazard Risk

Not applicable

3. Composition/information on ingredients

Product form

: Mixture

Substance name	Other Names	Product identifier number	Concentration (%)
Iron	Iron, elemental / Direct reduced Iron / Iron, reduced / Elemental iron / IRON POWDER / iron	CAS-No.: 7439-89-6 KECI-No.: KE-21059	43 – 48
Chromium	Chromium metal / Chromium, elemental / Chromium, metal / Chromium, metallic / Chrome, metal / Chrome	CAS-No.: 7440-47-3 KECI-No.: KE-05970	16 – 20
Titanium Dioxide	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO2) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / TITANIUM DIOXIDE / Titanium oxide / Titanium dioxide(2)	CAS-No.: 13463-67-7 KECI-No.: KE-33900	13 – 17

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Substance name	Other Names	Product identifier number	Concentration (%)
	Mica dust / Mica group minerals / Silicates, mica / C.I. 77019 / Mica- group minerals / MICA / C.I. Pigment White 20 / Pigment White 20	CAS-No.: 12001-26-2 KECI-No.: KE-25420	3 – 7
Nickel	Nickel metal / Nickel, elemental / Nickel, metallic / Nickel, metal / C.I. 77775	CAS-No.: 7440-02-0 KECI-No.: KE-25818	5 – 7
	Silicic acid, sodium salt / SODIUM SILICATE / Sodium silicates	CAS-No.: 1344-09-8 KECI-No.: KE-31002	1 – 5
	Feldspar, group minerals / Feldspar- group minerals / Feldspar-group minerals (An inorganic substance that is the reaction product of high temperature calcination in which aluminum oxide, barium oxide, calcium oxide, magnesium oxide, silicon oxide, and strontium oxide in varying amounts are homogeneously and ionically interdiffused to form a crystalline matrix.) / Aventurine / Feldspar mineral / Feldspars, Feldspar-group minerals / Feldspars,	CAS-No.: 68476-25-5 KECI-No.: KE-16962	1 – 3
	C.I. Pigment White 18 / Calcium carbonate / Pigment White 18 / C.I. 77220 / Carbonic acid, calcium salt / CALCIUM CARBONATE / CI 77220 / calcium carbonate	CAS-No.: 471-34-1 KECI-No.: KE-04487	1 – 3
Manganese	Manganese, elemental / Manganese metal / manganese	CAS-No.: 7439-96-5 KECI-No.: KE-22999	1 – 3

4. First-aid measures

4.1. First-aid measures after eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.

4.2. First-aid measures after skin contact

Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.

4.3. First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing.

4.4. First-aid measures after ingestion

Rinse mouth. Do not induce vomiting. Call a physician immediately.

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

4.5. Other medical advice or treatment

Treat symptomatically.

5. Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing	media	
5 5	: Water spray. Dry powder. Foam. : No data available	
5.2. Special hazards arising from the substan	nce or mixture	
No data available		
5.3. Special protective equipment and precautions for fire-fighters		
Protection during firefighting	 Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. 	

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate spillage area.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid contact with skin and eyes.

Do not attempt to take action without suitable protective equipment.

For further information refer to section 8: "Exposure controls/personal protection".

Dispose of materials or solid residues at an authorized site.

6.2. Environmental precautions and protective procedures

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Mechanically recover the product.

7. Handling and storage	
7.1. Precautions for safe handling	
, , , , , , , , , , , , , , , , , , ,	Ensure good ventilation of the work station. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures :	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage	
Storage conditions :	Store locked up. Store in a well-ventilated place. Keep cool.

8. Exposure controls/personal protection 8.1. Occupational Exposure Limits

Material Safety Data Sheet

KST-308L			
No data available			
(68476-25-5)			
No data available			
(471-34-1)			
Korea - Occupational Exposure Limits			
Local name	탄산칼슘 # Calcium carbonate		
ISHA OEL TWA	10 mg/m ³		
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48		
China - Occupational Exposure Limits			
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals		
Vietnam - Occupational Exposure Limits			
OEL TWA	10 mg/m ³		
Australia - Occupational Exposure Limits			
OES TWA [1]	10 mg/m ³ (containing no asbestos and <1% crystalline silica-inhalable dust)		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL TWA	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)		
(1344-09-8)	(1344-09-8)		
No data available			
Titanium Dioxide (13463-67-7)			
Korea - Occupational Exposure Limits			
Local name	이산화티타늄 # Titanium dioxide		
ISHA OEL TWA	10 mg/m ³		
Remark (KR)	발암성 2 # Carcinogenicity 2		
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48		
China - Occupational Exposure Limits			
OEL PC-TWA	8 mg/m³ (total dust)		
Chemical category	Possibly carcinogenic to humans dust		
Catalogue of Occupational Hazard Factors	Category 1 - Dusts		
Indonesia - Occupational Exposure Limits			
NAB (OEL TWA)	10 mg/m ³		
Chemical category	A4 - not classifiable as a human carcinogen		
Singapore - Occupational Exposure Limits			
PEL (OEL TWA)	10 mg/m ³		
Taiwan - Occupational Exposure Limits			
OEL TWA	10 mg/m ³		

Material Safety Data Sheet

Titanium Dioxide (13463-67-7)		
Vietnam - Occupational Exposure Limits		
OEL TWA	6 mg/m³ (inhalable dust) 5 mg/m³ (respirable dust)	
OEL STEL	10 mg/m³ (inhalable dust)	
Australia - Occupational Exposure Limits		
OES TWA [1]	10 mg/m ³ (containing no asbestos and <1% crystalline silica-inhalable dust)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	10 mg/m ³	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA - IDLH - Occupational Exposure Limits		
IDLH	5000 mg/m ³	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale)	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	15 mg/m³ (total dust)	
(12001-26-2)		
Korea - Occupational Exposure Limits		
Local name	운모 # Mica	
ISHA OEL TWA	3 mg/m³ 호흡성 # (Respirable fraction)	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
China - Occupational Exposure Limits		
OEL PC-TWA	2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust)	
Catalogue of Occupational Hazard Factors	Category 1 - Dusts	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	3 mg/m ³ (respirable particulate)	
Singapore - Occupational Exposure Limits		
PEL (OEL TWA)	3 mg/m ³ (respirable dust)	
Taiwan - Occupational Exposure Limits		
OEL TWA	3 mg/m³ (respirable dust)	
OEL STEL	6 mg/m ³ (respirable dust)	
Thailand - Occupational Exposure Limits	Fhailand - Occupational Exposure Limits	
OEL TWA	3 mg/m ³ (respirable dust)	
Australia - Occupational Exposure Limits		
OES TWA [1]	2.5 mg/m³ (inspirable)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	0.1 mg/m ³ (respirable particulate matter)	

Material Safety Data Sheet

(12001-26-2)		
USA - IDLH - Occupational Exposure Limits		
IDLH	1500 mg/m³ (containing <1% quartz)	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	3 mg/m³ (containing <1% Quartz-respirable dust)	
Iron (7439-89-6)		
Korea - Occupational Exposure Limits		
Local name	철염(가용성) # Iron salts (Soluble, as Fe)	
ISHA OEL TWA	1 mg/m ³	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
China - Occupational Exposure Limits		
Catalogue of Occupational Hazard Factors	Category 1 - Dusts	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	1 mg/m ³	
Manganese (7439-96-5)		
Korea - Occupational Exposure Limits		
Local name	망간 및 무기 화합물 # Manganese&Inorganic compounds, as Mn	
ISHA OEL TWA	1 mg/m³ 1 mg/m³ (吝) # (Fume)	
ISHA OEL STEL	3 mg/m³ (音) # (Fume)	
ISHA PEL TWA	1 mg/m ³	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
China - Occupational Exposure Limits		
OEL PC-TWA	0.15 mg/m ³	
OEL PC-TWA (Highly Toxic Goods)	0.15 mg/m³ (dust and fume)	
OEL PC-STEL (Highly Toxic Goods)	0.45 mg/m³ (dust and fume)	
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals	
India - Occupational Exposure Limits		
PEL (OEL TWA)	1 mg/m³ (fume)	
PEL (OEL STEL)	0.03 mg/m³ (fume)	
PEL (OEL C)	5 mg/m³ (dust)	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	0.1 mg/m³ (inhalable particulate) 0.02 mg/m³ (respirable particulate)	
Chemical category	A4 - not classifiable as a human carcinogen	
Singapore - Occupational Exposure Limits		
PEL (OEL TWA)	1 mg/m³ (dust and fume)	
OEL STEL	3 mg/m ³ (fume)	
Singapore - BTLV		
BTLV	50 μg/l Parameter: Manganese - Medium: urine	

Material Safety Data Sheet

Manganese (7439-96-5)			
Taiwan - Occupational Exposure Limits			
OEL TWA	1 mg/m ³ (category C3 special chemical-fume)		
OEL STEL	2 mg/m³ (category C3 special chemical-fume)		
OEL C	5 mg/m³ (category C3 special chemical)		
Vietnam - Occupational Exposure Limits			
OEL TWA	0.3 mg/m ³		
OEL STEL	0.6 mg/m ³		
Australia - Occupational Exposure Limits			
OES TWA [1]	1 mg/m³ (dust and fume)		
OES STEL	3 mg/m³ (fume)		
USA - ACGIH - Occupational Exposure Limits	·		
ACGIH OEL TWA	0.02 mg/m³ (respirable particulate matter) 0.1 mg/m³ (inhalable particulate matter)		
ACGIH chemical category	Not Classifiable as a Human Carcinogen		
USA - IDLH - Occupational Exposure Limits			
IDLH	500 mg/m ³		
USA - NIOSH - Occupational Exposure Limits	·		
NIOSH REL TWA	1 mg/m³ (fume)		
NIOSH REL STEL	3 mg/m ³		
USA - OSHA - Occupational Exposure Limits			
OSHA PEL C	5 mg/m ³ (fume)		
Nickel (7440-02-0)	Nickel (7440-02-0)		
Korea - Occupational Exposure Limits			
Local name	니켈 (금속) # Nickel (Metal)		
ISHA OEL TWA	1 mg/m³ (metal)		
ISHA PEL TWA	0.2 mg/m ³		
Remark (KR)	발암성 2 # Carcinogenicity 2		
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48		
China - Occupational Exposure Limits			
OEL PC-TWA	1 mg/m ³		
Chemical category	Possibly carcinogenic to humans		
OEL PC-TWA (Highly Toxic Goods)	1 mg/m ³		
OEL PC-STEL (Highly Toxic Goods)	2.5 mg/m ³		
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals		
Indonesia - Occupational Exposure Limits			
NAB (OEL TWA)	1.5 mg/m³ (inhalable particulate)		
Chemical category	A5 - not suspected as human carcinogen		
Singapore - Occupational Exposure Limits			
PEL (OEL TWA)	1 mg/m ³		

Material Safety Data Sheet

Nickel (7440-02-0)	
Taiwan - Occupational Exposure Limits	
OEL TWA	1 mg/m ³
OEL STEL	2 mg/m ³
Thailand - Occupational Exposure Limits	
OEL TWA	1 mg/m ³
Vietnam - Occupational Exposure Limits	
OEL TWA	0.05 mg/m ³
OEL STEL	0.25 mg/m ³
Australia - Occupational Exposure Limits	
OES TWA [1]	1 mg/m ³
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1.5 mg/m ³ (inhalable particulate matter)
ACGIH chemical category	Not Suspected as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	$5\mu\text{g/l}$ Parameter: Nickel - Medium: urine - Sampling time: post-shift at end of workweek (background)
USA - IDLH - Occupational Exposure Limits	
IDLH	10 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	0.015 mg/m ³
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	1 mg/m ³
Chromium (7440-47-3)	
Korea - Occupational Exposure Limits	
ISHA OEL TWA	0.5 mg/m³ (metal)
China - Occupational Exposure Limits	
OEL PC-TWA	0.05 mg/m ³
Chemical category	Sensitizer, Carcinogenic to humans
OEL PC-TWA (Highly Toxic Goods)	0.15 mg/m ³
OEL MAC (Highly Toxic Goods)	0.05 mg/m ³
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals
Indonesia - Occupational Exposure Limits	
NAB (OEL TWA)	0.5 mg/m ³
Chemical category	A4 - not classifiable as a human carcinogen
Singapore - Occupational Exposure Limits	
PEL (OEL TWA)	0.5 mg/m ³
Taiwan - Occupational Exposure Limits	
OEL TWA	1 mg/m ³
OEL STEL	2 mg/m ³

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Chromium (7440-47-3)		
Australia - Occupational Exposure Limits		
OES TWA [1]	0.5 mg/m³	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	0.5 mg/m³ (inhalable particulate matter)	
USA - ACGIH - Biological Exposure Indices	·	
BEI	0.7 μ g/l Parameter: Total chromium - Medium: urine - Sampling time: end of shift at end of workweek (population based)	
USA - IDLH - Occupational Exposure Limits		
IDLH	250 mg/m ³	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	0.5 mg/m ³	
USA - OSHA - Occupational Exposure Limits	·	
OSHA PEL TWA [1]	1 mg/m ³	
8.2. Appropriate engineering controls		
Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.		
8.3. Personal protection		
Respiratory protection:		
In case of insufficient ventilation, wear suitable respiratory equipment		
Eye protection:		
Safety glasses		
Hand protection:		
Hand protection: Protective gloves		
Skin and body protection:		
Wear suitable protective clothing		
Personal protective equipment symbol(s):		

9. Physica	l and chem	ical properties
------------	------------	-----------------

- a) Appearance
- Physical state
- b) Odour
- c) Odour threshold
- d) pH
- e) Melting / freezing point
- f) Initial boiling point and boiling range

KR - en

: No data available / Not applicable

: No data available

No data availableNo data available

: No data available

: No data available

: Solid

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

g) h) i) j)	Flash point Evaporation rate Flammability (solid, gas) Upper / lower flammability or explosive limits	:	No data available No data available No data available No data available
k)	Vapour pressure	:	No data available
I)	Solubility	:	No data available
m)	Vapour density	:	No data available
n)	Relative density	:	No data available
o)	Partition coefficient n-octanol/water	:	No data available
p)	Auto-ignition temperature	:	No data available
q)	Decomposition temperature	:	No data available
r)	Viscosity, kinematic	:	No data available
	Viscosity, dynamic	:	No data available
s)	Molecular mass	:	No data available

10. Stability and reactivity

10.1. Chemical stability and Possibility of hazardous reactions

The product is non-reactive under normal conditions of use, storage and transport.

Stable under normal conditions.

No dangerous reactions known under normal conditions of use.

10.2. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.3. Incompatible materials

No data available

10.4. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

11.1. Information on exposure routes	
Oral	: Not classified
Skin and eyes contact	: Causes severe skin burns. Causes serious eye damage. May cause an allergic skin reaction.
Inhalation	: May cause allergic reactions, asthma or shortness of breath and etc if inhaled.
11.2. Health hazards	
Acute toxicity (oral):	
Not classified	
Acute toxicity (dermal):	
Not classified	
Acute toxicity (inhalation):	
Not classified	

(471-34-1)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

(471-34-1)	
LC50 Inhalation - Rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
(1344-09-8)	
LD50 oral rat	3400 mg/kg Source: SIDS

LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.06 mg/l air Animal: rat, Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
LC50 Inhalation - Rat (Dust/Mist)	> 3.43 mg/l Source: ECHA

(12001-26-2)	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)

Iron (7439-89-6)	
LD50 oral rat	98600 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 250 mg/m³ air (6 h, Rat, Male, Experimental value, Inhalation (dust))

Manganese (7439-96-5)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LC50 Inhalation - Rat	> 5.14 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation))
LC50 Inhalation - Rat (Dust/Mist)	> 5.14 mg/l Source: ECHA

Nickel (7440-02-0)	
LD50 oral rat	> 9000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 10.2 mg/l (Exposure time: 1 h)

Chromium (7440-47-3)	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 420, Rat, Male / female, Read- across, Oral, 14 day(s))
LC50 Inhalation - Rat	> 5.41 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 5.41 mg/l Source: ECHA

Skin corrosion/irritation:

Causes severe skin burns.

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Serious eye damage/irritation:

Causes serious eye damage.

Respiratory sensitization:

May cause allergic reactions, asthma or shortness of breath and etc if inhaled.

Skin sensitization:

May cause an allergic skin reaction.

Carcinogenicity:

Suspected of causing cancer.

	(68476-25-5)	
IARC group 1 - Carcinogenic to humans	1 - Carcinogenic to humans	

Titanium Dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Nickel (7440-02-0)

IARC group	2B - Possibly carcinogenic to humans

Chromium (7440-47-3)	
IARC group	3 - Not classifiable

Mutagenicity:

Not classified

Reproductive toxicity:

Not classified

STOT-single exposure:

Not classified

STOT-repeated exposure:

Causes damage to organs through prolonged or repeated exposure.

(471-34-1)

(471-04-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	\geq 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Nickel (7440-02-0)	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.004 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Chromium (7440-47-3)

LOAEC (inhalation, rat,dust/mist/fume, 90 days)	\geq 0.0044 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard:

Not classified

Material Safety Data Sheet

(471-34-1)		
Viscosity, kinematic (calculated value) (40 $^\circ$ C)	Not applicable (solid)	
Density	2.7 – 2.9 g/cm³ (at 20 °C)	
Viscosity, kinematic	Not applicable (solid)	
Viscosity, dynamic	Not applicable (solid)	
(1344-09-8)		
Density	1350 – 1380 kg/m³	
Titanium Dioxide (13463-67-7)		
Viscosity, kinematic (calculated value) (40 °C)	Not applicable (solid)	
Density	3.9 – 4.1 g/cm ³	
Viscosity, kinematic	Not applicable (solid)	
Viscosity, dynamic	Not applicable (solid)	
Iron (7439-89-6)		
Density	7.87 g/cm ³ Type: 'density' Temp.: 20 °C	
Manganese (7439-96-5)		
Density	7200 kg/m ³	
Nickel (7440-02-0)		
Viscosity, kinematic (calculated value) (40 °C)	Not applicable (solid)	
Density	8.9 g/cm³ (at 25 °C)	
Viscosity, kinematic	Not applicable (solid)	
Viscosity, dynamic	Not applicable (solid)	
Chromium (7440-47-3)		
Density	7.19 g/cm³ (at 20 °C)	

12. Ecological information	
12.1. Ecotoxicity	
Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.
(474 34 4)	

(471-34-1)	
LC50 - Fish [1]	> 56000 mg/l Source: ECOTOX
EC50 - Crustacea [1]	> 100 % (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)

Material Safety Data Sheet

(471-34-1)	
EC50 96h - Algae [1]	22000 mg/l Source: Ecological Structure Activity Relationships
EC50 72h - Algae [1]	 > 14 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
BCF - Fish [1]	(no bioaccumulation)

(1344-09-8)	
LC50 - Fish [1]	1108 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	3185 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
EC50 - Crustacea [1]	1700 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	160 mg/l (96 h, Amphipoda)
EC50 72h - Algae [1]	207 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 345.4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
BCF - Fish [1]	(no bioaccumulation expected)

Titanium Dioxide (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Iron (7439-89-6)	
LC50 - Fish [1]	8.65 mg/l Source: ECHA
LC50 - Other aquatic organisms [1]	106.3 mg/l Source: ECHA
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	> 10000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	18 mg/l Source: ECHA

Manganese (7439-96-5)	
LC50 - Fish [1]	> 3.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1.6 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Manganese (7439-96-5)	
EC50 72h - Algae [2]	2.8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '8 d'
BCF - Fish [1]	81 (Pisces)
BCF - Other aquatic organisms [1]	300000 (Mollusca)
BCF - Other aquatic organisms [2]	125000 (Crustacea)

Nickel (7440-02-0)	
LC50 - Fish [1]	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
LC50 - Fish [2]	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 - Crustacea [1]	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 96h - Algae [1]	0.174 – 0.311 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 72h - Algae [1]	0.18 mg/l (Species: Pseudokirchneriella subcapitata)
BCF - Other aquatic organisms [1]	8 - 45 (≤ 4 week(s), Cambarus sp., Flow-through system, Fresh water, Experimental value, Fresh weight)

Chromium (7440-47-3)	
LC50 - Fish [1]	13.9 – 210 mg/l Source: GESTIS
EC50 - Crustacea [1]	17.7 – 18.9 mg/l Source: ECHA
EC50 72h - Algae [1]	0.1 – 17.8 mg/l Source: GESTIS
BCF - Fish [1]	0.0048 (Pisces, Literature study, Dry weight)
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC

12.2. Persistence and degradability

(68476-25-5)	
Persistence and degradability	Biodegradability in soil: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

(471-34-1)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

(1344-09-8)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130				
(1344-09-8)				
BOD (% of ThOD)	Not applicable			
Titanium Dioxide (13463-67-7)				
Persistence and degradability	Biodegradability: not applicable.			
Chemical oxygen demand (COD)	Not applicable (inorganic)			
ThOD	Not applicable (inorganic)			
(12001-26-2)				
Persistence and degradability	Biodegradability: not applicable.			
Chemical oxygen demand (COD)	Not applicable (inorganic)			
ThOD	Not applicable (inorganic)			
	·			
Iron (7439-89-6)				
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
BOD (% of ThOD)	Not applicable			
Manganese (7439-96-5)				
Persistence and degradability	Biodegradability: not applicable.			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
BOD (% of ThOD)	Not applicable			
Nickel (7440-02-0)				
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.			
Chemical oxygen demand (COD)	Not applicable (inorganic)			
ThOD	Not applicable (inorganic)			
Chromium (7440-47-3)				
Persistence and degradability	Biodegradability: not applicable.			
Chemical oxygen demand (COD)	Not applicable (inorganic)			
ThOD	Not applicable (inorganic)			
12.3. Bioaccumulative potential				
(68476-25-5)				
Bioaccumulative potential	No bioaccumulation data available.			
(474.24.4)				
(471-34-1)				
BCF - Fish [1]	(no bioaccumulation)			

Material Safety Data Sheet

(471-34-1)		
Bioaccumulative potential	Not bioaccumulative.	
· · · · · · · · · · · · · · · · · · ·		
(1344-09-8)		
BCF - Fish [1]	(no bioaccumulation expected)	
Bioaccumulative potential	Bioaccumulation: not applicable.	
Titanium Dioxide (13463-67-7)		
Bioaccumulative potential	Not bioaccumulative.	
(12001-26-2)		
Bioaccumulative potential	No bioaccumulation data available.	
Iron (7439-89-6)		
Bioaccumulative potential	No bioaccumulation data available.	
Manganese (7439-96-5)		
BCF - Fish [1]	81 (Pisces)	
BCF - Other aquatic organisms [1]	300000 (Mollusca)	
BCF - Other aquatic organisms [2]	125000 (Crustacea)	
Bioaccumulative potential	No bioaccumulation data available.	
Nickel (7440-02-0)		
BCF - Other aquatic organisms [1]	$8-45$ (\leq 4 week(s), Cambarus sp., Flow-through system, Fresh water, Experimental value, Fresh weight)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
Chromium (7440-47-3)		
BCF - Fish [1]	0.0048 (Pisces, Literature study, Dry weight)	
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC	
Bioaccumulative potential	Not bioaccumulative.	
12.4. Mobility in soil		
(471-34-1)		
Mobility in soil	4.971 Source: Quantitative Structure Activity Relation	
Surface tension	No data available (test not performed)	
Ecology - soil	Low potential for adsorption in soil.	
(1344-09-8)		
Ecology - soil	No (test)data on mobility of the component(s) available.	
Titanium Dioxide (13463-67-7)		
Surface tension	No data available in the literature	
L		

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

ow potential for mobility in soil.
o (test)data on mobility of the substance available.
0

Iron (7439-89-6)	
Surface tension	Not applicable (solid)
Ecology - soil	Adsorbs into the soil.

Manganese (7439-96-5)	
Ecology - soil	No (test)data on mobility of the substance available.

Nickel (7440-02-0)		
Surface tension Not applicable (solid)		
Ecology - soil No (test)data on mobility of the substance available.		

Chromium (7440-47-3)	
Surface tension	No data available (test not performed)
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC
Ecology - soil	No (test)data on mobility of the substance available.
12.5. Other adverse effects	
Ozone	: Not classified

Ozone . Not classified Other adverse effects : No data available

13. Disposal considerations

13.1. Disposal method

Dispose of contents/container in accordance with licensed collector's sorting instructions.

13.2. Disposal precaution

No data available

14. Transport information

UN RTDG	ADR	IMDG	IATA
14.1. UN number			
Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

UN RTDG	ADR	IMDG	IATA
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Marine pollutant			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

No data available

15. Regulatory information		
15.1. Occupational Safety and Health Act		
Hazardous Substances Prohibited for Manufacturing Hazardous Substances Requiring Permission Threshold Limit Values Chemicals	Not applicable Not applicable Applicable	13463-67-7: Titanium dioxide 12001-26-2: Mica 7439-89-6: Iron salts (Soluble, as Fe) 7439-96-5: Manganese&Inorganic compounds, as Mn 7440-02-0: Nickel 7440-47-3: Chromium
Hazardous Substances Below Permissible Level	Applicable	7439-96-5: Manganese and its inorganic compounds 7440-02-0: Nickel and its insoluble inorganic compounds
Hazardous Substances Subject to Working Environment Measurement	Applicable	13463-67-7: Titanium dioxide 12001-26-2: Mica 7439-96-5: Manganese and its inorganic compounds 7440-02-0: Nickel and its inorganic compounds 7440-47-3: Chromium and its inorganic compounds
Hazardous Substances Subject to Workers Requiring Health Examination	Applicable	7439-96-5: Manganese and its inorganic compounds 7440-02-0: Nickel and its inorganic compounds 7440-47-3: Chromium and its compounds
Hazardous Substances Subject to Control	Applicable	13463-67-7: Titanium dioxide 7439-89-6: Iron and its compounds 7439-96-5: Manganese and its inorganic compounds 7440-02-0: Nickel and its inorganic compounds 7440-47-3: Chromium and its compounds(except Chromium(VI) compounds)

15.2. Chemicals Control Act

No data available

15.3. ACT ON REGISTRATION, EVALUATION, ETC. OF CHEMICALS (K-REACH)

No data available

15.4. Safety Control of Dangerous Substa	nces Act	
Safety Control of Dangerous Substances Act	Applicable	(Class 2 Combustible solid - category 4 Iron Powder (Designated quantity: 500kg); Class 2 Combustible solid - category 5 Metal powder (Designated quantity: 500kg))
	Applicable	7439-89-6: Iron powder (Class 2 Combustible solid - category 4 Iron Powder (Designated quantity: 500kg)) 7439-96-5: Manganese powder (Class 2 Combustible solid - category 5 Metal powder (Designated quantity: 500kg))

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

7440-47-3: Chromium powder (Class 2 Combustible solid - category 5 Metal powder (Designated quantity: 500kg))

15.5. Wastes Control Act Hazardous Substances in Designated wastes Not applicable Types of wastes No data available **15.6.** Other Domestic and International Regulatory Information **Domestic** Persistent Organic Pollutants(POPs) Control Act Not applicable Ozone Depleting Substances(ODS) Not applicable International **EU Regulatory Information** EU Candidate list (SVHC) Contains no substance on the REACH candidate list EU authorization list (REACH Annex XIV) Contains no REACH Annex XIV substances EU restriction list (REACH Annex XVII) Not applicable **US Regulatory Information** CERCLA Section 103 (40CFR302.4) Contains listed substances EPCRA Section 302 (40CFR355.30) Not applicable EPCRA Section 304 (40CFR355.40) Not applicable EPCRA Section 313 (40CFR372.65) Contains listed substances International agreements No data available 16. Other information REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE 16.1. Data sources: COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006, Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013, ECHA (European Chemicals Agency), Supplier's safety documents, No data available, This MSDS is prepared based on Article 41 of the Occupational Safety and Health Act and Notice No.2016-19 of the Ministry of Employment and Labor (based on the availability of material safety and health data), taking into account the status of regulations related to Korea, This MSDS is prepared based on KOSHA, NITE, ESIS, NLM, SIDS, IPCS, NCIS, etc, This safety data sheet was compiled with data and information from the following sources : RTECS, ECOSAR, HSDB, SIDS SIAP, ChemWATCH, CESAR, Chemical DB. 11/3/2020 16.2. Issue date: 1.0, 29/12/2021 16.3. Revision number and date: No data available 16.4. Other information:

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.