

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

MSDS Number: AA06900-0000000218 Issue date: 11/3/2020 Revision date: 12/29/2021 Version: 1.0

1. Chemical product and company identification

1.1. Product identifier

Product form : Mixture
Trade name : KST-309LMo

1.2. Recommended uses and restrictions

Use Categories

35 - Welding and soldering products, flux products

1.2.1. Recommended use

Welding and soldering products, flux products.

1.2.2. Restrictions on use

1.3. Supplier information

- Supplier

Company : KISWEL

Address : (51544) South Korea 704, Gongdan-ro, Seongsan-gu, Changwon-si, Gyeongnam, Korea

Tel. : 055)269-7200 Fax : 055)266-4487

2. Hazards identification

2.1. Classification of the substance or mixture

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 1	H318
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity - Repeated exposure, Category 1	H372
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

2.2. Label elements

2.2.1. Hazard pictograms (GHS KR)







2.2.2. Signal word (GHS KR)

Danger.

2.2.3. Hazard statements (GHS KR)

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H334 - May cause allergic reactions, asthma or shortness of breath and etc if inhaled.

H351 - Suspected of causing cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

H412 - Harmful to aquatic life with long lasting effects.

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

2.2.4. Precautionary statements (GHS KR)

Precaution:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands, forearms and face thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P284 Wear respiratory protection.

Treatment:

P302+P352 - IF ON SKIN: Wash with plenty of water/....

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER/doctor/....

P314 - Get medical advice/attention if you feel unwell.

P321 - Take ... treatment.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER/doctor/....

P362+P364 - Take off contaminated clothing and wash it before reuse.

Storage:

P405 - Store locked up.

Disposal:

P501 - Dispose of contents/container according to waste related regulations.

2.3. Hazards - Other hazards which do not result in classification - Hazard Risk

Not applicable

3. Composition/information on ingredients

Product form : Mixture

Substance name	Other Names	Product identifier number	Concentration (%)
Iron	Iron, elemental / Direct reduced Iron / Iron, reduced / Elemental iron / IRON POWDER / iron	CAS-No.: 7439-89-6 KECI-No.: KE-21059	41 – 45
Chromium	Chromium metal / Chromium, elemental / Chromium, metal / Chromium, metallic / Chrome, metal / Chrome	CAS-No.: 7440-47-3 KECI-No.: KE-05970	16 – 20
Titanium Dioxide	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO2) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / TITANIUM DIOXIDE / Titanium oxide / Titanium dioxide(2)	CAS-No.: 13463-67-7 KECI-No.: KE-33900	9 – 12

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Substance name	Other Names	Product identifier number	Concentration (%)
Nickel	Nickel metal / Nickel, elemental / Nickel, metallic / Nickel, metal / C.I. 77775	CAS-No.: 7440-02-0 KECI-No.: KE-25818	8 – 10
	C.I. Pigment White 18 / Calcium carbonate / Pigment White 18 / C.I. 77220 / Carbonic acid, calcium salt / CALCIUM CARBONATE / CI 77220 / calcium carbonate	CAS-No.: 471-34-1 KECI-No.: KE-04487	1 – 5
	Mica dust / Mica group minerals / Silicates, mica / C.I. 77019 / Mica- group minerals / MICA / C.I. Pigment White 20 / Pigment White 20	CAS-No.: 12001-26-2 KECI-No.: KE-25420	1 – 5
	Feldspar, group minerals / Feldspar-group minerals / Feldspar-group minerals (An inorganic substance that is the reaction product of high temperature calcination in which aluminum oxide, barium oxide, calcium oxide, magnesium oxide, silicon oxide, and strontium oxide in varying amounts are homogeneously and ionically interdiffused to form a crystalline matrix.) / Aventurine / Feldspar mineral / Feldspars, Feldspar-group minerals / Feldspars, feldspar-group minerals	CAS-No.: 68476-25-5 KECI-No.: KE-16962	0.5 – 3
CaF2	Calcium fluoride / Fluorspar / FLUORSPAR / CALCIUM FLUORIDE / Calcium difluoride / calcium fluoride	CAS-No.: 7789-75-5 KECI-No.: KE-04538	0.5 – 3
	Silicic acid, sodium salt / SODIUM SILICATE / Sodium silicates	CAS-No.: 1344-09-8 KECI-No.: KE-31002	1 – 3
Manganese	Manganese, elemental / Manganese metal / manganese	CAS-No.: 7439-96-5 KECI-No.: KE-22999	1 – 3
Molybdenum	Molybdenum metal / Molybdenum, elemental / Molybdenum, metal / Molybdenum, metallic / molybdenum	CAS-No.: 7439-98-7 KECI-No.: KE-25427	1 – 3

4. First-aid measures

4.1. First-aid measures after eye contact

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Call a physician immediately.

4.2. First-aid measures after skin contact

Wash skin with plenty of water.

Take off contaminated clothing.

If skin irritation occurs: Get medical advice/attention.

4.3. First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing.

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

4.4. First-aid measures after ingestion

Call a poison center or a doctor if you feel unwell.

4.5. Other medical advice or treatment

Treat symptomatically.

5. Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

Unsuitable extinguishing media : No data available

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate spillage area.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid contact with skin and eyes.

Do not attempt to take action without suitable protective equipment.

For further information refer to section 8: "Exposure controls/personal protection".

Dispose of materials or solid residues at an authorized site.

6.2. Environmental precautions and protective procedures

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Mechanically recover the product.

7. Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid contact with skin and eyes.

Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse.

Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage

Storage conditions : Store in a well-ventilated place.

Keep cool.

12/29/2021 (Revision date) KR - en 4/24

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Catalogue of Occupational Hazard Factors

8. Exposure controls/personal protection	8. Exposure controls/personal protection		
8.1. Occupational Exposure Limits			
KST-309LMo			
No data available			
(68476-25-5)			
No data available			
(471-34-1)			
Korea - Occupational Exposure Limits			
Local name	탄산칼슘 # Calcium carbonate		
ISHA OEL TWA	10 mg/m³		
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48		
China - Occupational Exposure Limits			
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals		
Vietnam - Occupational Exposure Limits			
OEL TWA	10 mg/m³		
Australia - Occupational Exposure Limits			
OES TWA [1]	10 mg/m³ (containing no asbestos and <1% crystalline silica-inhalable dust)		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL TWA	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)		
CaF2 (7789-75-5)			
China - Occupational Exposure Limits			
OEL PC-TWA	0.7 mg/m³ (mixed dust, respirable) 1 mg/m³ (mixed dust, total)		
Catalogue of Occupational Hazard Factors	Category 1 - Dusts		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	2.5 mg/m³		
(1344-09-8)			
No data available			
Titanium Dioxide (13463-67-7)			
Korea - Occupational Exposure Limits			
Local name	이산화티타늄 # Titanium dioxide		
ISHA OEL TWA	10 mg/m³		
Remark (KR)	발암성 2 # Carcinogenicity 2		
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48		
China - Occupational Exposure Limits			
OEL PC-TWA	8 mg/m³ (total dust)		
Chemical category	Possibly carcinogenic to humans dust		

Category 1 - Dusts

Material Safety Data Sheet

NAB (OEL TWA) 10 mg/m² Chemical category A4 - not classifiable as a human carcinogen Singapore - Occupational Exposure Limits PEL (OEL TWA) 10 mg/m² Taiwan - Occupational Exposure Limits OEL TWA 10 mg/m² OEL STEL 15 mg/m² Vietnam - Occupational Exposure Limits OEL TWA 5 mg/m² (inhalable dust) 5 mg/m² (respirable dust) OEL STEL 10 mg/m² (inhalable dust) 5 mg/m² (inhalable dust) OEL STEL 10 mg/m² (inhalable dust) 10 mg/m² (inhalabl	Titanium Dioxide (13463-67-7)		
Chemical category A4 - not classifiable as a human carcinogen Singapore - Occupational Exposure Limits PEL (OEL TWA) 10 mg/m² Taliwan - Occupational Exposure Limits OEL TWA 10 mg/m² OEL STEL 15 mg/m² Viotnam - Occupational Exposure Limits OEL TWA 6 mg/m² (inhalable dust) 5 mg/m² (respirable dust) OEL STEL 10 mg/m² (containing no asbestos and <1% crystalline silica-inhalable dust) OES TWA[1] 10 mg/m² (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 10 mg/m² ACGIH chemical category Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m² USA - NOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m² (CIB 63-fine) 0.3 mg/m² (CIB 63-fi	Indonesia - Occupational Exposure Limits		
Singapore - Occupational Exposure Limits PEL (OEL TWA) 10 mg/m² Talwan - Occupational Exposure Limits OEL TWA 10 mg/m² OEL STEL 15 mg/m² Viotnam - Occupational Exposure Limits OEL TWA 6 mg/m² (inhalable dust) 5 mg/m² (respirable dust) OEL STEL 10 mg/m² (containing no asbestos and <1% crystalline silica-inhalable dust) OES TWA 10 mg/m² (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH OEL TWA 10 mg/m² (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH OEL TWA 10 mg/m² (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH OEL TWA 10 mg/m² (containing no asbestos and <1% crystalline silica-inhalable dust) USA - IDLH - Occupational Exposure Limits USA - IDLH - Occupational Exposure Limits USA - NIOSH - Occupational Exposure Limits USA - NIOSH - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m² (cital dust) (12001-26-2) Korea - Occupational Exposure Limits USA - OSHA - Occupational Exposure Limits OSHA OEL TWA 3 mg/m² 조존생 # (Respirable fraction) 교史노동가고시 제 2020-48 호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m² (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	NAB (OEL TWA)	10 mg/m³	
PEL (ØEL TWA) 10 mg/m² Taiwan - Occupational Exposure Limits ØEL TWA 10 mg/m² ØEL STEL 15 mg/m² ØEL STEL 15 mg/m² ØEL STEL 15 mg/m² (inhalable dust) ØEL STEL 10 mg/m² (inhalable dust) ØEL FWA (inhalable dust) ØEL STEL 10 mg/m² (inhalable dust) ØEL FWA (inhalable du	Chemical category	A4 - not classifiable as a human carcinogen	
Talwan - Occupational Exposure Limits OEL TWA 10 mg/m¹ OEL STEL 15 mg/m¹ Vietnam - Occupational Exposure Limits OEL TWA 6 mg/m² (inhalable dust) 5 mg/m² (respirable dust) OEL STEL 10 mg/m² (inhalable dust) Australia - Occupational Exposure Limits OES TWA [1] 10 mg/m² (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 10 mg/m² Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m² USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m² (CIB 63-dine) 0.3 mg/m² (CIB 63-dine) 0.3 mg/m² (CIB 63-dire) including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m² (total dust) (12001-26-2) Korea - Occupational Exposure Limits USHA OEL TWA 3 mg/m² .5 % # (Respirable fraction) 3 mg/m² .5 % # (Respirable fraction) 3 mg/m² .5 % # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m² (total dust) 1.5 mg/m² (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	Singapore - Occupational Exposure Limits		
DEL TWA 10 mg/m³ OEL STEL 15 mg/m² Vietnam - Occupational Exposure Limits OEL TWA 6 mg/m³ (inhalable dust) 5 mg/m² (respirable dust) 5 mg/m² (respirable dust) OEL STEL 10 mg/m³ (inhalable dust) OEL STEL 10 mg/m³ (inhalable dust) Australia - Occupational Exposure Limits OES TWA [1] 10 mg/m³ (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 10 mg/m³ ACGIH Chemical category Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m³ (CIB 63-fine) 0.3 mg/m² (CIB 63-line) 0.3 mg/m² (CIB 63-line) including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name 2.	PEL (OEL TWA)	10 mg/m³	
Section 15 mg/m²	Taiwan - Occupational Exposure Limits		
Vietnam - Occupational Exposure Limits 6 mg/m³ (inhalable dust) 5 mg/m³ (respirable dust)	OEL TWA	10 mg/m³	
OEL TWA 8 mg/m² (inhalable dust) 5 mg/m² (respirable dust) OEL STEL 10 mg/m² (respirable dust) OEL STEL 10 mg/m² (inhalable dust) Australia - Occupational Exposure Limits OES TWA [1] 10 mg/m³ (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 10 mg/m³ ACGIH othenical category Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 0.3 mg/m² (CIB 63-fine) 0.3 mg/m² (CIB 63-fine) 0.3 mg/m² (CIB 63-tiltrafine, including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name ②모 # Mica 3 mg/m² 호급성 # (Respirable fraction) Regulatory reference 고송노중각교시 제2020-48호 # MOEL Public Notice, No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m² (respirable dust) 1.5 mg/m² (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	OEL STEL	15 mg/m³	
S mg/m² (respirable dust) OEL STEL 10 mg/m² (inhalable dust) Australia - Occupational Exposure Limits OES TWA [1] 10 mg/m² (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 10 mg/m² ACGIH chemical category Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m² USA - NIOSH - Occupational Exposure Limits IDLH 5000 mg/m² USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m² (CIB 63-fine) 0.3 mg/m² (CIB 63-line) 0.3 mg/m² (CIB 63-line) 1.5 mg/m² (total dust) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m² (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name ②모 # Mica ISHA OEL TWA 3 mg/m² 호흡생 # (Respirable fraction) Regulatory reference 고용노동부교서 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m² (total dust) 1.5 mg/m² (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	Vietnam - Occupational Exposure Limits		
Australia - Occupational Exposure Limits OES TWA [1] 10 mg/m³ (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 10 mg/m³ ACGIH chemical category Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ditrafine, including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits USA - Occupational Exposure Limits Local name \$\frac{\pi_{\pi}}{\pi_{\pi}} \frac{\pi_{\pi}}{\pi_{\pi_{\pi_{\pi_{\pi_{\pi_{\pi_{\pi_	OEL TWA		
DES TWA [1] 10 mg/m³ (containing no asbestos and <1% crystalline silica-inhalable dust) USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA 10 mg/m³ Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name 오토 # Mica 3 mg/m³ 호흡생 # (Respirable fraction) Regulatory reference 교용노동부교시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	OEL STEL	10 mg/m³ (inhalable dust)	
USA - ACGIH - Occupational Exposure Limits ACGIH OEL TWA ACGIH Chemical category Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name 2.4 mg/m³ & (Respirable fraction) Regulatory reference 2.8 노동부과시 제2020-48 호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (total dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	Australia - Occupational Exposure Limits		
ACGIH OEL TWA 10 mg/m³ ACGIH chemical category Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name & & & & & & & & & & & & & & & & & & &	OES TWA [1]	10 mg/m³ (containing no asbestos and <1% crystalline silica-inhalable dust)	
Not Classifiable as a Human Carcinogen USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name 2.4 mg/m³ (ERspirable fraction) Regulatory reference 2.8 x \(\frac{1}{2} \) x \(\frac{1}{2}	USA - ACGIH - Occupational Exposure Limits		
USA - IDLH - Occupational Exposure Limits IDLH 5000 mg/m³ USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name 2모 # Mica ISHA OEL TWA 3 mg/m³ 호흡성 # (Respirable fraction) Regulatory reference 2모 ***	ACGIH OEL TWA	10 mg/m³	
SUSA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name 원모 # Mica ISHA OEL TWA 3 mg/m³ 호흡성 # (Respirable fraction) Regulatory reference 고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (respirable dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA - NIOSH - Occupational Exposure Limits NIOSH REL TWA 2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale) USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name ② 里 # Mica ISHA OEL TWA ③ mg/m³ 호흡성 # (Respirable fraction) Regulatory reference □ 교육노동부교시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA ② mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	USA - IDLH - Occupational Exposure Limits		
USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name 오무 # Mica ISHA OEL TWA 3 mg/m³ 호흡성 # (Respirable fraction) Regulatory reference 고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	IDLH	5000 mg/m³	
USA - OSHA - Occupational Exposure Limits OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name 운모 # Mica ISHA OEL TWA 3 mg/m³ 호흡성 # (Respirable fraction) Regulatory reference 고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	USA - NIOSH - Occupational Exposure Limits		
OSHA PEL TWA [1] 15 mg/m³ (total dust) (12001-26-2) Korea - Occupational Exposure Limits Local name 오모 # Mica ISHA OEL TWA 3 mg/m³ 호흡성 # (Respirable fraction) Regulatory reference 고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	NIOSH REL TWA		
(12001-26-2) Korea - Occupational Exposure Limits Local name 운모 # Mica ISHA OEL TWA 3 mg/m³ 호흡성 # (Respirable fraction) Regulatory reference 고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	USA - OSHA - Occupational Exposure Limits		
Korea - Occupational Exposure Limits Local name 요모#Mica ISHA OEL TWA 3 mg/m³ 호흡성 # (Respirable fraction) Regulatory reference 교용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	OSHA PEL TWA [1]	15 mg/m³ (total dust)	
BLOCAI name 운모 # Mica ISHA OEL TWA 3 mg/m³ 호흡성 # (Respirable fraction) Regulatory reference 고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	(12001-26-2)		
ISHA OEL TWA 3 mg/m³ 호흡성 # (Respirable fraction) Regulatory reference 고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	Korea - Occupational Exposure Limits		
Regulatory reference 고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48 China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	Local name	운모#Mica	
China - Occupational Exposure Limits OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	ISHA OEL TWA	3 mg/m³ 호흡성 # (Respirable fraction)	
OEL PC-TWA 2 mg/m³ (total dust) 1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
1.5 mg/m³ (respirable dust) Catalogue of Occupational Hazard Factors Category 1 - Dusts	China - Occupational Exposure Limits		
	OEL PC-TWA		
Indonesia - Occupational Exposure Limits	Catalogue of Occupational Hazard Factors	Category 1 - Dusts	
	Indonesia - Occupational Exposure Limits		
NAB (OEL TWA) 3 mg/m³ (respirable particulate)	NAB (OEL TWA)	3 mg/m³ (respirable particulate)	
Singapore - Occupational Exposure Limits	Singapore - Occupational Exposure Limits		
PEL (OEL TWA) 3 mg/m³ (respirable dust)	PEL (OEL TWA)	3 mg/m³ (respirable dust)	
Taiwan - Occupational Exposure Limits			
OEL TWA 3 mg/m³ (respirable dust)	OEL TWA	3 mg/m³ (respirable dust)	

Material Safety Data Sheet

(12001-26-2)	
OEL STEL	6 mg/m³ (respirable dust)
Thailand - Occupational Exposure Limits	
OEL TWA	3 mg/m³ (respirable dust)
Australia - Occupational Exposure Limits	
OES TWA [1]	2.5 mg/m³ (inspirable)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.1 mg/m³ (respirable particulate matter)
USA - IDLH - Occupational Exposure Limits	
IDLH	1500 mg/m³ (containing <1% quartz)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	3 mg/m³ (containing <1% Quartz-respirable dust)
Iron (7439-89-6)	
Korea - Occupational Exposure Limits	
Local name	철염(가용성) # Iron salts (Soluble, as Fe)
ISHA OEL TWA	1 mg/m³
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48
China - Occupational Exposure Limits	
Catalogue of Occupational Hazard Factors	Category 1 - Dusts
Indonesia - Occupational Exposure Limits	
NAB (OEL TWA)	1 mg/m³
Manganese (7439-96-5)	
Korea - Occupational Exposure Limits	
Local name	망간 및 무기 화합물 # Manganese&Inorganic compounds, as Mn
ISHA OEL TWA	1 mg/m³ 1 mg/m³ (音) # (Fume)
ISHA OEL STEL	3 mg/m³ (荼) # (Fume)
ISHA PEL TWA	1 mg/m³
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48
China - Occupational Exposure Limits	
OEL PC-TWA	0.15 mg/m³
OEL PC-TWA (Highly Toxic Goods)	0.15 mg/m³ (dust and fume)
OEL PC-STEL (Highly Toxic Goods)	0.45 mg/m³ (dust and fume)
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals
India - Occupational Exposure Limits	
PEL (OEL TWA)	1 mg/m³ (fume)
PEL (OEL STEL)	0.03 mg/m³ (fume)
PEL (OEL C)	5 mg/m³ (dust)

Material Safety Data Sheet

Manganese (7439-96-5)		
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	0.1 mg/m³ (inhalable particulate) 0.02 mg/m³ (respirable particulate)	
Chemical category	A4 - not classifiable as a human carcinogen	
Singapore - Occupational Exposure Limits		
PEL (OEL TWA)	1 mg/m³ (dust and fume)	
OEL STEL	3 mg/m³ (fume)	
Singapore - BTLV		
BTLV	50 μg/l Parameter: Manganese - Medium: urine	
Taiwan - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (category C3 special chemical-fume)	
OEL STEL	2 mg/m³ (category C3 special chemical-fume)	
OEL C	5 mg/m³ (category C3 special chemical)	
Vietnam - Occupational Exposure Limits		
OEL TWA	0.3 mg/m ³	
OEL STEL	0.6 mg/m³	
Australia - Occupational Exposure Limits		
OES TWA [1]	1 mg/m³ (dust and fume)	
OES STEL	3 mg/m³ (fume)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	0.02 mg/m³ (respirable particulate matter) 0.1 mg/m³ (inhalable particulate matter)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA - IDLH - Occupational Exposure Limits		
IDLH	500 mg/m³	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	1 mg/m³ (fume)	
NIOSH REL STEL	3 mg/m³	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL C	5 mg/m³ (fume)	
Nickel (7440-02-0)		
Korea - Occupational Exposure Limits		
Local name	니켈 (금속) # Nickel (Metal)	
ISHA OEL TWA	1 mg/m³ (metal)	
ISHA PEL TWA	0.2 mg/m³	
Remark (KR)	발암성 2 # Carcinogenicity 2	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
China - Occupational Exposure Limits		
OEL PC-TWA	1 mg/m³	

Material Safety Data Sheet

Nickel (7440-02-0)	
Chemical category	Possibly carcinogenic to humans
OEL PC-TWA (Highly Toxic Goods)	1 mg/m³
OEL PC-STEL (Highly Toxic Goods)	2.5 mg/m ³
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals
Indonesia - Occupational Exposure Limits	
NAB (OEL TWA)	1.5 mg/m³ (inhalable particulate)
Chemical category	A5 - not suspected as human carcinogen
Singapore - Occupational Exposure Limits	
PEL (OEL TWA)	1 mg/m³
Taiwan - Occupational Exposure Limits	
OEL TWA	1 mg/m³
OEL STEL	2 mg/m³
Thailand - Occupational Exposure Limits	
OEL TWA	1 mg/m³
Vietnam - Occupational Exposure Limits	
OEL TWA	0.05 mg/m³
OEL STEL	0.25 mg/m³
Australia - Occupational Exposure Limits	
OES TWA [1]	1 mg/m³
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1.5 mg/m³ (inhalable particulate matter)
ACGIH chemical category	Not Suspected as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	5 μg/l Parameter: Nickel - Medium: urine - Sampling time: post-shift at end of workweek (background)
USA - IDLH - Occupational Exposure Limits	
IDLH	10 mg/m³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	0.015 mg/m ³
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	1 mg/m³
Chromium (7440-47-3)	
Korea - Occupational Exposure Limits	
ISHA OEL TWA	0.5 mg/m³ (metal)
China - Occupational Exposure Limits	
OEL PC-TWA	0.05 mg/m³
Chemical category	Sensitizer, Carcinogenic to humans
OEL PC-TWA (Highly Toxic Goods)	0.15 mg/m³
OEL MAC (Highly Toxic Goods)	0.05 mg/m³

Material Safety Data Sheet

Chromium (7440-47-3)		
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	0.5 mg/m³	
Chemical category	A4 - not classifiable as a human carcinogen	
Singapore - Occupational Exposure Limits		
PEL (OEL TWA)	0.5 mg/m³	
Taiwan - Occupational Exposure Limits		
OEL TWA	1 mg/m³	
OEL STEL	2 mg/m³	
Australia - Occupational Exposure Limits		
OES TWA [1]	0.5 mg/m ³	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	0.5 mg/m³ (inhalable particulate matter)	
USA - ACGIH - Biological Exposure Indices		
BEI	$0.7~\mu g/I$ Parameter: Total chromium - Medium: urine - Sampling time: end of shift at end of workweek (population based)	
USA - IDLH - Occupational Exposure Limits		
IDLH	250 mg/m³	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	0.5 mg/m ³	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	1 mg/m³	
Molybdenum (7439-98-7)		
Korea - Occupational Exposure Limits		
Local name	몰리브덴 (불용성화합물) # Molybdenum (Insoluble compounds)	
ISHA OEL TWA	10 mg/m³ 흡입성 # (Inhalable fraction) 5 mg/m³ 호흡성 # (Respirable fraction)	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	5 mg/m³ (respirable particulate)	
Chemical category	A3 - confirmed animal carcinogen	
Australia - Occupational Exposure Limits		
OES TWA [1]	10 mg/m³	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	10 mg/m³ (inhalable particulate matter) 3 mg/m³ (respirable particulate matter)	
USA - IDLH - Occupational Exposure Limits		
IDLH	5000 mg/m³	

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Personal protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Eye protection:

Safety glasses

Hand protection:

Protective gloves

Skin and body protection:

Wear suitable protective clothing

Personal protective equipment symbol(s):







9. Physical and chemical properties

a) Appearance : No data available

Physical state : Solid

b) Odourc) Odour thresholddata availabledata available

d) pH : No data available

e) Melting / freezing point : No data available / Not applicable

Initial boiling point and boiling range : No data available f) Flash point : No data available g) Evaporation rate : No data available h) : No data available i) Flammability (solid, gas) Upper / lower flammability or explosive limits : No data available i) k) Vapour pressure : No data available I) Solubility : No data available

 I)
 Solubility
 : No data available

 m)
 Vapour density
 : No data available

 n)
 Relative density
 : No data available

 o)
 Partition coefficient n-octanol/water
 : No data available

 p)
 Auto-ignition temperature
 : No data available

 q)
 Decomposition temperature
 : No data available

 r)
 Viscosity, kinematic
 : No data available

Viscosity, dynamic : No data available s) Molecular mass : No data available

10. Stability and reactivity

10.1. Chemical stability and Possibility of hazardous reactions

The product is non-reactive under normal conditions of use, storage and transport.

Stable under normal conditions.

No dangerous reactions known under normal conditions of use.

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

10.2. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.3. Incompatible materials

No data available

10.4. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

11.1. Information on exposure routes

Oral : Not classified

Skin and eyes contact : Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction.

Inhalation : May cause allergic reactions, asthma or shortness of breath and etc if inhaled.

11.2. Health hazards

Acute toxicity (oral):

Not classified

Acute toxicity (dermal):

Not classified

Acute toxicity (inhalation):

Not classified

(471-34-1)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

CaF2 (7789-75-5)	
LD50 oral rat	4250 mg/kg
LC50 Inhalation - Rat	> 5.07 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

(1344-09-8)	
LD50 oral rat	3400 mg/kg Source: SIDS
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 2.06 mg/l air Animal: rat, Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Titanium Dioxide (13463-67-7)	
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
LC50 Inhalation - Rat (Dust/Mist)	> 3.43 mg/l Source: ECHA

(12001-26-2)	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)

Iron (7439-89-6)	
LD50 oral rat	98600 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 250 mg/m³ air (6 h, Rat, Male, Experimental value, Inhalation (dust))

Manganese (7439-96-5)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LC50 Inhalation - Rat	> 5.14 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation))
LC50 Inhalation - Rat (Dust/Mist)	> 5.14 mg/l Source: ECHA

Nickel (7440-02-0)	
LD50 oral rat	> 9000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 10.2 mg/l (Exposure time: 1 h)

Chromium (7440-47-3)	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 420, Rat, Male / female, Readacross, Oral, 14 day(s))
LC50 Inhalation - Rat	> 5.41 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 5.41 mg/l Source: ECHA

Molybdenum (7439-98-7)	
LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 5.84 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	> 3.92 mg/l Source: ECHA

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye damage.

Respiratory sensitization:

May cause allergic reactions, asthma or shortness of breath and etc if inhaled.

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Skin sensitization:

May cause an allergic skin reaction.

Carcinogenicity:

Suspected of causing cancer.

(68476-25-5)	
IARC group	1 - Carcinogenic to humans

Titanium Dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Nickel (7440-02-0)	
IARC group	2B - Possibly carcinogenic to humans

Chromium (7440-47-3)	
IARC group	3 - Not classifiable

Mutagenicity:

Not classified

Reproductive toxicity:

Not classified

STOT-single exposure:

Not classified

STOT-repeated exposure:

Causes damage to organs through prolonged or repeated exposure.

(471-34-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Nickel (7440-02-0)	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.004 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Chromium (7440-47-3)	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	≥ 0.0044 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Molybdenum (7439-98-7)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.1 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Aspiration hazard:

Not classified

(471-34-1)	
Viscosity, kinematic (calculated value) (40 °C)	Not applicable (solid)
Density	2.7 – 2.9 g/cm³ (at 20 °C)
Viscosity, kinematic	Not applicable (solid)
Viscosity, dynamic	Not applicable (solid)

CaF2 (7789-75-5)	
Density	3.18 g/cm³ Type: 'density'

(1344-09-8)	
Density	1350 – 1380 kg/m³

Titanium Dioxide (13463-67-7)	
Viscosity, kinematic (calculated value) (40 °C)	Not applicable (solid)
Density	3.9 – 4.1 g/cm ³
Viscosity, kinematic	Not applicable (solid)
Viscosity, dynamic	Not applicable (solid)

Iron (7439-89-6)	
Density	7.87 g/cm³ Type: 'density' Temp.: 20 °C

Manganese (7439-96-5)	
Density	7200 kg/m³

Nickel (7440-02-0)	
Viscosity, kinematic (calculated value) (40 °C)	Not applicable (solid)
Density	8.9 g/cm³ (at 25 °C)
Viscosity, kinematic	Not applicable (solid)
Viscosity, dynamic	Not applicable (solid)

Chromium (7440-47-3)	
Density	7.19 g/cm³ (at 20 °C)

Molybdenum (7439-98-7)	
Density	10.2 g/cm³ (at 20 °C)

12. Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

12/29/2021 (Revision date) KR - en 15/24

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Hazardous to the aquatic environment, short-term

(acute)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)

: Not classified

(471-34-1)	
LC50 - Fish [1]	> 56000 mg/l Source: ECOTOX
EC50 - Crustacea [1]	> 100 % (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	22000 mg/l Source: Ecological Structure Activity Relationships
EC50 72h - Algae [1]	> 14 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
BCF - Fish [1]	(no bioaccumulation)

CaF2 (7789-75-5)	
LC50 - Fish [1]	51 mg/l Test organisms (species): other:summary of finidngs in various species
LC50 - Fish [2]	165 mg/l Test organisms (species): other:summary of finidngs in various species
EC50 - Crustacea [1]	97 – 270 mg/l (48 h, Daphnia magna, Static system, Fresh water, Literature, Fluorine ion)
EC50 96h - Algae [1]	7444.076 mg/l Source: Ecological Structure Activity Relationships
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	14.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	4 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '21 d'

(1344-09-8)	
LC50 - Fish [1]	1108 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	3185 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
EC50 - Crustacea [1]	1700 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	160 mg/l (96 h, Amphipoda)
EC50 72h - Algae [1]	207 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	> 345.4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
BCF - Fish [1]	(no bioaccumulation expected)

Titanium Dioxide (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Material Safety Data Sheet

Titanium Dioxide (13463-67-7)	
ErC50 algae	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Iron (7439-89-6)	
LC50 - Fish [1]	8.65 mg/l Source: ECHA
LC50 - Other aquatic organisms [1]	106.3 mg/l Source: ECHA
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	> 10000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	18 mg/l Source: ECHA

Manganese (7439-96-5)	
LC50 - Fish [1]	> 3.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1.6 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	2.8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '8 d'
BCF - Fish [1]	81 (Pisces)
BCF - Other aquatic organisms [1]	300000 (Mollusca)
BCF - Other aquatic organisms [2]	125000 (Crustacea)

Nickel (7440-02-0)	
LC50 - Fish [1]	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
LC50 - Fish [2]	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 - Crustacea [1]	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 96h - Algae [1]	0.174 – 0.311 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 72h - Algae [1]	0.18 mg/l (Species: Pseudokirchneriella subcapitata)
BCF - Other aquatic organisms [1]	8 – 45 (≤ 4 week(s), Cambarus sp., Flow-through system, Fresh water, Experimental value, Fresh weight)

Chromium (7440-47-3)	
LC50 - Fish [1]	13.9 – 210 mg/l Source: GESTIS
EC50 - Crustacea [1]	17.7 – 18.9 mg/l Source: ECHA
EC50 72h - Algae [1]	0.1 – 17.8 mg/l Source: GESTIS
BCF - Fish [1]	0.0048 (Pisces, Literature study, Dry weight)
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Molybdenum (7439-98-7)	
LC50 - Fish [1]	609.1 mg/l Source: EHCA
EC50 72h - Algae [1]	289.2 mg/l Source: ECHA
BCF - Fish [1]	260 – 500 (Tilapia rendalli)
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC Access on Jan 2006

12.2. Persistence and degradability

(68476-25-5)	
Persistence and degradability	Biodegradability in soil: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

(471-34-1)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

CaF2 (7789-75-5)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

(1344-09-8)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Titanium Dioxide (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

(12001-26-2)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Iron (7439-89-6)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Manganese (7439-96-5)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Nickel (7440-02-0)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

Chromium (7440-47-3)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

Molybdenum (7439-98-7)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

(68476-25-5)	
Bioaccumulative potential	No bioaccumulation data available.

(471-34-1)		
BCF - Fish [1]	(no bioaccumulation)	
Bioaccumulative potential	Not bioaccumulative.	

CaF2 (7789-75-5)	
Bioaccumulative potential	No bioaccumulation data available.

(1344-09-8)	
BCF - Fish [1]	(no bioaccumulation expected)

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130			
(1344-09-8)			
Bioaccumulative potential	e potential Bioaccumulation: not applicable.		
Titorium Diavida (42402 07.7)			
itanium Dioxide (13463-67-7)			
Bioaccumulative potential	Not bioaccumulative.		
(12001-26-2)			
Bioaccumulative potential	No bioaccumulation data available.		
Iron (7439-89-6)			
Bioaccumulative potential	No bioaccumulation data available.		
Manganese (7439-96-5)			
BCF - Fish [1]	81 (Pisces)		
BCF - Other aquatic organisms [1]	300000 (Mollusca)		
BCF - Other aquatic organisms [2]	125000 (Crustacea)		
Bioaccumulative potential	No bioaccumulation data available.		
Nickel (7440-02-0)			
·	2. 45 (44 mode). October on Florida mode for the state for		
BCF - Other aquatic organisms [1]	$8-45 \ (\le 4 \ week(s), \ Cambarus \ sp., \ Flow-through \ system, \ Fresh \ water, \ Experimental \ value, \ Fresh \ weight)$		
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
Chromium (7440-47-3)			
BCF - Fish [1]	0.0048 (Pisces, Literature study, Dry weight)		
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC		
Bioaccumulative potential	Not bioaccumulative.		
Mark de 2000 (7.400 00 7)			
Molybdenum (7439-98-7)			
BCF - Fish [1]	260 – 500 (Tilapia rendalli)		
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC Access on Jan 2006		
Bioaccumulative potential	No bioaccumulation data available.		
12.4. Mobility in soil			
(471-34-1)			
Mobility in soil	4.971 Source: Quantitative Structure Activity Relation		
Surface tension	No data available (test not performed)		
Ecology - soil	Low potential for adsorption in soil.		
CaF2 (7789-75-5)			
Ecology - soil	No (test)data on mobility of the substance available.		

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

(1344-09-8)	
Ecology - soil	No (test)data on mobility of the component(s) available.

Titanium Dioxide (13463-67-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

(12001-26-2)	
Ecology - soil	No (test)data on mobility of the substance available.

Iron (7439-89-6)	
Surface tension Not applicable (solid)	
Ecology - soil	Adsorbs into the soil.

Manganese (7439-96-5)	
Ecology - soil	No (test)data on mobility of the substance available.

Nickel (7440-02-0)	
Surface tension Not applicable (solid)	
Ecology - soil No (test)data on mobility of the substance available.	

Chromium (7440-47-3)	
Surface tension No data available (test not performed)	
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC
Ecology - soil No (test)data on mobility of the substance available.	

Molybdenum (7439-98-7)	
Partition coefficient n-octanol/water (Log Pow) 0.23 Source: SRC Access on Jan 2006	
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No data available

13. Disposal considerations

13.1. Disposal method

Dispose of contents/container in accordance with licensed collector's sorting instructions.

13.2. Disposal precaution

No data available

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

14. Transport information

UN RTDG	ADR	IMDG	IATA
14.1. UN number			
Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Marine pollutant			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

No data available

15. Regulatory information

15.1. Occupational Safety and Health Act

Hazardous Substances Prohibited for Manufacturing	Not applicable	
Hazardous Substances Requiring Permission	Not applicable	
Threshold Limit Values Chemicals	Applicable	13463-67-7: Titanium dioxide
		12001-26-2: Mica
		7439-89-6: Iron salts (Soluble, as Fe)
		7439-96-5: Manganese&Inorganic compounds, as Mn
		7440-02-0: Nickel
		7440-47-3: Chromium
		7439-98-7: Molybdenum alloys (as Mo)
Hazardous Substances Below Permissible Level	Applicable	7439-96-5: Manganese and its inorganic compounds
		7440-02-0: Nickel and its insoluble inorganic compounds
Hazardous Substances Subject to Working	Applicable	13463-67-7: Titanium dioxide
Environment Measurement		12001-26-2: Mica
		7439-96-5: Manganese and its inorganic compounds
		7440-02-0: Nickel and its inorganic compounds
		7440-47-3: Chromium and its inorganic compounds
Hazardous Substances Subject to Workers Requiring Health Examination	Applicable	7439-96-5: Manganese and its inorganic compounds
		7440-02-0: Nickel and its inorganic compounds
		7440-47-3: Chromium and its compounds
Hazardous Substances Subject to Control	Applicable	13463-67-7: Titanium dioxide
		7439-89-6: Iron and its compounds
		7439-96-5: Manganese and its inorganic compounds
		7440-02-0: Nickel and its inorganic compounds
		7440-47-3: Chromium and its compounds(except Chromium(VI)
		compounds)

15.2. Chemicals Control Act

No data available

15.3. ACT ON REGISTRATION, EVALUATION, ETC. OF CHEMICALS (K-REACH)

No data available

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

15.4. Safety Control of Dangerous Substances Act

Safety Control of Dangerous Substances Act

Applicable

(Class 2 Combustible solid - category 4 Iron Powder (Designated quantity: 500kg); Class 2 Combustible solid - category 5 Metal powder (Designated

quantity: 500kg))

Applicable 7439-89-6: Iron powder

(Class 2 Combustible solid - category 4 Iron Powder (Designated quantity:

500kg))

7439-96-5: Manganese powder

(Class 2 Combustible solid - category 5 Metal powder (Designated quantity:

500kg))

7440-47-3: Chromium powder

(Class 2 Combustible solid - category 5 Metal powder (Designated quantity:

500kg))

7439-98-7: Molybdenum powder

(Class 2 Combustible solid - category 5 Metal powder (Designated quantity:

500kg))

Contains no substance on the REACH candidate list

15.5. Wastes Control Act

Hazardous Substances in Designated wastes

Types of wastes

Not applicable
No data available

15.6. Other Domestic and International Regulatory Information

Domestic

Persistent Organic Pollutants(POPs) Control Act

Ozone Depleting Substances(ODS)

Not applicable Not applicable

International

EU Regulatory Information

EU Candidate list (SVHC)

EU authorization list (REACH Annex XIV)

EU restriction list (REACH Annex XVII)

Contains no REACH Annex XIV substances Not applicable

US Regulatory Information

CERCLA Section 103 (40CFR302.4)

EPCRA Section 302 (40CFR355.30)

EPCRA Section 304 (40CFR355.40)

EPCRA Section 313 (40CFR372.65)

Contains listed substances

Not applicable

Not applicable

Contains listed substances

International agreements

No data available

12/29/2021 (Revision date) KR - en 23/24

Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

16. Other information

16.1. Data sources:

16.2. Issue date:

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006, Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013, ECHA (European Chemicals Agency), Supplier's safety documents, No data available, This MSDS is prepared based on Article 41 of the Occupational Safety and Health Act and Notice No.2016-19 of the Ministry of Employment and Labor (based on the availability of material safety and health data), taking into account the status of regulations related to Korea, This MSDS is prepared based on KOSHA, NITE, ESIS, NLM, SIDS, IPCS, NCIS, etc, This safety data sheet was compiled with data and information from the following sources: RTECS, ECOSAR, HSDB, SIDS SIAP, ChemWATCH, CESAR, Chemical DB.

11/3/2020

16.3. Revision number and date: 1.0, 29/12/2021 **16.4. Other information:** No data available

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.