

Material Safety Data Sheet In Accordance with MOEL Public notice No 2020-130 MSDS Number: AA06900-0000000044 Issue date: 6/5/2011 Revision date: 2/16/2023 Version: 4.0

1. Chemical product and com	pany identification
1.1. Product identifier	
Product form Trade name	: Mixture : T-316L
1.2. Recommended uses and res	strictions
Use Categories 35 - Welding and soldering products, flu	ux products
<b>1.2.1. Recommended use</b> Welding and soldering products, flux pro	oducts.

1.2.2. Restrictions on use

1.3. Supplier information	
- Supplier	
Company	: KISWEL
Address	: (51544) South Korea 704, Gongdan-ro, Seongsan-gu, Changwon-si, Gyeongnam, Korea
Tel.	: 055)269-7200

- : 055)269-7200
- : 055)266-4487

2. Hazards identification	
2.1. Classification of the substance or mixture	
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity - Repeated exposure, Category 1	H372
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

### 2.2. Label elements

#### 2.2.1. Hazard pictograms (GHS KR)



#### 2.2.2. Signal word (GHS KR)

Danger.

Fax

#### 2.2.3. Hazard statements (GHS KR)

- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

#### 2.2.4. Precautionary statements (GHS KR)

### **Precaution:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands, forearms and face thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

#### **Treatment:**

P302+P352 - IF ON SKIN: Wash with plenty of water/....

P308+P313 - IF exposed or concerned: Get medical advice/attention.

- P314 Get medical advice/attention if you feel unwell.
- P321 Take ... treatment.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

Storage:

P405 - Store locked up.

#### **Disposal:**

P501 - Dispose of contents/container according to waste related regulations.

#### 2.3. Hazards - Other hazards which do not result in classification - Hazard Risk

Not applicable

### 3. Composition/information on ingredients

Product form

: Mixture

Substance name	Other Names	Product identifier number	Concentration (%)
Iron	Iron, elemental / Direct reduced Iron / Iron, reduced / Elemental iron / IRON POWDER / iron	CAS-No.: 7439-89-6 KECI-No.: KE-21059	59.8 - 67.7
Chromium	Chromium metal / Chromium, elemental / Chromium, metal / Chromium, metallic / Chrome, metal / Chrome	CAS-No.: 7440-47-3 KECI-No.: KE-05970	18 – 20
Nickel	Nickel metal / Nickel, elemental / Nickel, metallic / Nickel, metal / C.I. 77775	CAS-No.: 7440-02-0 KECI-No.: KE-25818	11 – 13.5
Molybdenum	Molybdenum metal / Molybdenum, elemental / Molybdenum, metal / Molybdenum, metallic / molybdenum	CAS-No.: 7439-98-7 KECI-No.: KE-25427	2 – 3
Manganese	Manganese, elemental / Manganese metal / manganese	CAS-No.: 7439-96-5 KECI-No.: KE-22999	1 – 2.5
Silicon Metal	Silicon powder / Silicon powder, amorphous / Ammonium hexafluorosilicate / SILICON / silicon	CAS-No.: 7440-21-3 KECI-No.: KE-31029	0.3 – 0.7

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Substance name	Other Names	Product identifier number	Concentration (%)
Copper	C.I. 77400 / C.I. Pigment Metal 2 / Copper, elemental / CI 77400 / Copper metal / Copper, metallic / Pigment Metal 2 / Granulated copper / copper	CAS-No.: 7440-50-8 KECI-No.: KE-08896	≤ 0.5

### 4. First-aid measures

### 4.1. First-aid measures after eye contact

Rinse eyes with water as a precaution.

Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

4.3. First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing.

4.4. First-aid measures after ingestion

Call a poison center or a doctor if you feel unwell.

4.5. Other medical advice or treatment

Treat symptomatically.

5. Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	: Water spray. Dry powder. Foam. : No data available	
5.2. Special hazards arising from the substance or mixture		
No data available		
5.3. Special protective equipment and preca	autions for fire-fighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate spillage area.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid contact with skin and eyes.

Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Dispose of materials or solid residues at an authorized site.

### 6.2. Environmental precautions and protective procedures

Avoid release to the environment.

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

### 6.3. Methods and material for containment and cleaning up

Mechanically recover the product.

Notify authorities if product enters sewers or public waters.

7. Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	<ul> <li>Ensure good ventilation of the work station.</li> <li>Obtain special instructions before use.</li> <li>Do not handle until all safety precautions have been read and understood.</li> <li>Wear personal protective equipment.</li> <li>Do not breathe dust/fume/gas/mist/vapours/spray.</li> <li>Avoid contact with skin and eyes.</li> </ul>
Hygiene measures	<ul> <li>Contaminated work clothing should not be allowed out of the workplace.</li> <li>Wash contaminated clothing before reuse.</li> <li>Do not eat, drink or smoke when using this product.</li> <li>Always wash hands after handling the product.</li> </ul>
7.2. Conditions for safe storage	
Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.

## 8. Exposure controls/personal protection

8.1. Occupational Exposure Limits		
T-316L		
No data available		
Silicon Metal (7440-21-3)		
Korea - Occupational Exposure Limits		
Local name	실리콘 # Silicon	
ISHA OEL TWA	10 mg/m <sup>3</sup>	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	(OEL TWA) 10 mg/m <sup>3</sup> (not containing Asbestos and the crystal content is <1%)	
Singapore - Occupational Exposure Limits		
PEL (OEL TWA)	EL (OEL TWA) 10 mg/m <sup>3</sup>	
Australia - Occupational Exposure Limits		
OES TWA [1]	10 mg/m <sup>3</sup> (containing no asbestos and <1% crystalline silica-inhalable dust)	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)	

# Material Safety Data Sheet

Manganese (7439-96-5)		
Korea - Occupational Exposure Limits		
Local name	망간 및 무기 화합물 # Manganese&Inorganic compounds, as Mn	
ISHA OEL TWA	1 mg/m³ 1 mg/m³ (吝) # (Fume)	
ISHA OEL STEL	3 mg/m³ (吝) # (Fume)	
ISHA PEL TWA	1 mg/m <sup>3</sup>	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
China - Occupational Exposure Limits		
OEL PC-TWA	0.15 mg/m <sup>3</sup>	
OEL PC-TWA (Highly Toxic Goods)	0.15 mg/m³ (dust and fume)	
OEL PC-STEL (Highly Toxic Goods)	0.45 mg/m³ (dust and fume)	
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals	
India - Occupational Exposure Limits		
PEL (OEL TWA)	1 mg/m³ (fume)	
PEL (OEL STEL)	0.03 mg/m³ (fume)	
PEL (OEL C)	5 mg/m³ (dust)	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	0.1 mg/m³ (inhalable particulate) 0.02 mg/m³ (respirable particulate)	
Chemical category	A4 - not classifiable as a human carcinogen	
Singapore - Occupational Exposure Limits		
PEL (OEL TWA)	1 mg/m³ (dust and fume)	
OEL STEL	3 mg/m³ (fume)	
Singapore - BTLV	·	
BTLV	50 μg/l Parameter: Manganese - Medium: urine	
Taiwan - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (category C3 special chemical-fume)	
OEL STEL	2 mg/m³ (category C3 special chemical-fume)	
OEL C	5 mg/m³ (category C3 special chemical)	
Vietnam - Occupational Exposure Limits		
OEL TWA	0.3 mg/m <sup>3</sup>	
OEL STEL	0.6 mg/m <sup>3</sup>	
Australia - Occupational Exposure Limits		
OES TWA [1]	1 mg/m³ (dust and fume)	
OES STEL	3 mg/m³ (fume)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	0.02 mg/m³ (respirable particulate matter) 0.1 mg/m³ (inhalable particulate matter)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	

# Material Safety Data Sheet

Manganese (7439-96-5)		
USA - IDLH - Occupational Exposure Limits		
IDLH	500 mg/m <sup>3</sup>	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	1 mg/m³ (fume)	
NIOSH REL STEL	3 mg/m <sup>3</sup>	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL C	5 mg/m³ (fume)	
Copper (7440-50-8)		
Korea - Occupational Exposure Limits		
Local name	구리 # Copper	
ISHA OEL TWA	1 mg/m³ (분진 및 미스트) # (Dust & mist, as Cu) 0.1 mg/m³ (흄) # (Fume)	
ISHA OEL STEL	2 mg/m³ (분진 및 미스트) # (Dust & mist, as Cu)	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
China - Occupational Exposure Limits		
OEL PC-TWA	1 mg/m³ (dust) 0.2 mg/m³ (fume)	
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals	
India - Occupational Exposure Limits		
PEL (OEL TWA)	0.2 mg/m <sup>3</sup> (fume)	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	1 mg/m³ (dust and mist) 0.2 mg/m³ (fume)	
Singapore - Occupational Exposure Limits		
PEL (OEL TWA)	0.2 mg/m³ (fume) 1 mg/m³ (dust and mist)	
Taiwan - Occupational Exposure Limits		
OEL TWA	0.2 mg/m³ (fume) 1 mg/m³ (dust and mist)	
OEL STEL	0.6 mg/m³ (fume) 2 mg/m³ (dust and mist)	
Vietnam - Occupational Exposure Limits		
OEL TWA	0.5 mg/m³ (dust) 0.1 mg/m³ (fume)	
OEL STEL	1 mg/m <sup>3</sup> (dust) 0.2 mg/m <sup>3</sup> (fume)	
Australia - Occupational Exposure Limits		
OES TWA [1]	1 mg/m³ (dust and mist) 0.2 mg/m³ (fume)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	0.2 mg/m <sup>3</sup> (fume)	

# Material Safety Data Sheet

Copper (7440-50-8)		
USA - IDLH - Occupational Exposure Limits		
IDLH	100 mg/m³ (dust, fume and mist)	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	1 mg/m³ (dust and mist) 0.1 mg/m³ (fume)	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	0.1 mg/m <sup>3</sup> (fume) 1 mg/m <sup>3</sup> (dust and mist)	
Nickel (7440-02-0)		
Korea - Occupational Exposure Limits		
Local name	니켈 (금속) # Nickel (Metal)	
ISHA OEL TWA	1 mg/m³ (metal)	
ISHA PEL TWA	0.2 mg/m <sup>3</sup>	
Remark (KR)	발암성 2 # Carcinogenicity 2	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
China - Occupational Exposure Limits		
OEL PC-TWA	1 mg/m <sup>3</sup>	
Chemical category	Possibly carcinogenic to humans	
OEL PC-TWA (Highly Toxic Goods)	1 mg/m <sup>3</sup>	
OEL PC-STEL (Highly Toxic Goods)	2.5 mg/m <sup>3</sup>	
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	1.5 mg/m <sup>3</sup> (inhalable particulate)	
Chemical category	A5 - not suspected as human carcinogen	
Singapore - Occupational Exposure Limits		
PEL (OEL TWA)	1 mg/m <sup>3</sup>	
Taiwan - Occupational Exposure Limits		
OEL TWA	1 mg/m <sup>3</sup>	
OEL STEL	2 mg/m <sup>3</sup>	
Thailand - Occupational Exposure Limits		
OEL TWA	1 mg/m <sup>3</sup>	
Vietnam - Occupational Exposure Limits		
OEL TWA	0.05 mg/m <sup>3</sup>	
OEL STEL	0.25 mg/m <sup>3</sup>	
Australia - Occupational Exposure Limits		
OES TWA [1]	1 mg/m <sup>3</sup>	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	1.5 mg/m <sup>3</sup> (inhalable particulate matter)	
ACGIH chemical category	Not Suspected as a Human Carcinogen	

# Material Safety Data Sheet

Nickel (7440-02-0)		
USA - ACGIH - Biological Exposure Indices		
BEI	$5\mu\text{g/l}$ Parameter: Nickel - Medium: urine - Sampling time: post-shift at end of workweek (background)	
USA - IDLH - Occupational Exposure Limits		
IDLH	10 mg/m <sup>3</sup>	
USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	0.015 mg/m <sup>3</sup>	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	1 mg/m <sup>3</sup>	
Molybdenum (7439-98-7)		
Korea - Occupational Exposure Limits		
Local name	몰리브덴 (불용성화합물) # Molybdenum (Insoluble compounds)	
ISHA OEL TWA	10 mg/m³ 흡입성 # (Inhalable fraction) 5 mg/m³ 호흡성 # (Respirable fraction)	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	5 mg/m <sup>3</sup> (respirable particulate)	
Chemical category	A3 - confirmed animal carcinogen	
Australia - Occupational Exposure Limits		
OES TWA [1]	10 mg/m <sup>3</sup>	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	10 mg/m <sup>3</sup> (inhalable particulate matter) 3 mg/m <sup>3</sup> (respirable particulate matter)	
USA - IDLH - Occupational Exposure Limits		
IDLH	5000 mg/m <sup>3</sup>	
Iron (7439-89-6)		
Korea - Occupational Exposure Limits		
Local name	철염(가용성)#Iron salts (Soluble, as Fe)	
ISHA OEL TWA	1 mg/m <sup>3</sup>	
Regulatory reference	고용노동부고시 제2020-48호 # MOEL Public Notice. No. 2020-48	
China - Occupational Exposure Limits		
Catalogue of Occupational Hazard Factors	Category 1 - Dusts	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	1 mg/m <sup>3</sup>	
Chromium (7440-47-3)		
Korea - Occupational Exposure Limits		
ISHA OEL TWA	0.5 mg/m³ (metal)	
China - Occupational Exposure Limits	·	
OEL PC-TWA	0.05 mg/m <sup>3</sup>	

# Material Safety Data Sheet

Chromium (7440-47-3)		
Chemical category	Sensitizer, Carcinogenic to humans	
OEL PC-TWA (Highly Toxic Goods)	0.15 mg/m <sup>3</sup>	
OEL MAC (Highly Toxic Goods)	0.05 mg/m <sup>3</sup>	
Catalogue of Occupational Hazard Factors	Category 3 - Chemicals	
Indonesia - Occupational Exposure Limits		
NAB (OEL TWA)	0.5 mg/m³	
Chemical category	A4 - not classifiable as a human carcinogen	
Singapore - Occupational Exposure Limits		
PEL (OEL TWA)	0.5 mg/m <sup>3</sup>	
Taiwan - Occupational Exposure Limits		
OEL TWA	1 mg/m <sup>3</sup>	
OEL STEL	2 mg/m <sup>3</sup>	
Australia - Occupational Exposure Limits		
OES TWA [1]	0.5 mg/m <sup>3</sup>	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	0.5 mg/m³ (inhalable particulate matter)	
USA - ACGIH - Biological Exposure Indices		
BEI	$0.7~\mu\text{g/I}$ Parameter: Total chromium - Medium: urine - Sampling time: end of shift at end of workweek (population based)	
USA - IDLH - Occupational Exposure Limits		
IDLH	250 mg/m <sup>3</sup>	
USA - NIOSH - Occupational Exposure Limits	·	
NIOSH REL TWA	0.5 mg/m <sup>3</sup>	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	1 mg/m <sup>3</sup>	
8.2. Appropriate engineering controls		
Appropriate engineering controls:Environmental exposure controls:	Ensure good ventilation of the work station. Avoid release to the environment.	
8.3. Personal protection		
Respiratory protection:		
In case of insufficient ventilation, wear suitable respiratory equipment		
Eye protection:		
Safety glasses		
Hand protection:		
Protective gloves		

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

#### Skin and body protection:

Wear suitable protective clothing

#### Personal protective equipment symbol(s):



### 9. Physical and chemical properties

a) Appearance	a)	Appearance
---------------	----	------------

- Physical state
- b) Odour
- c) Odour threshold
- d) pH
- e) Melting / freezing point
- f) Initial boiling point and boiling range
- g) Flash point
- h) Evaporation rate
- i) Flammability (solid, gas)
- j) Upper / lower flammability or explosive limits
- k) Vapour pressure
- Solubility
- m) Vapour density
- n) Relative density
- o) Partition coefficient n-octanol/water
- p) Auto-ignition temperature
- q) Decomposition temperature
- r) Viscosity, kinematic Viscosity, dynamic
- s) Molecular mass

### 10. Stability and reactivity

#### 10.1. Chemical stability and Possibility of hazardous reactions

The product is non-reactive under normal conditions of use, storage and transport. Stable under normal conditions.

No dangerous reactions known under normal conditions of use.

10.2. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### **10.3. Incompatible materials**

#### No data available

**10.4. Hazardous decomposition products** 

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

: No data available

: No data available

: No data available

: No data available

No data availableNot applicable

: No data available

: No data available

No data availableNo data available

No data availableNo data available

: No data available

: No data available

: No data available

: Not applicable

: Not applicable

: Non flammable.

: Not applicable

: No data available / Not applicable

Solid

11. Toxicological information	
11.1. Information on exposure routes	
Oral Skin and eyes contact Inhalation	<ul> <li>Not classified</li> <li>May cause an allergic skin reaction.</li> <li>Not classified</li> </ul>

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

## 11.2. Health hazards

### Acute toxicity (oral):

Not classified

## Acute toxicity (dermal):

Not classified

#### Acute toxicity (inhalation):

Not classified

Silicon Metal (7440-21-3)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit

Manganese (7439-96-5)	
LD50 oral rat	<ul> <li>&gt; 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline</li> <li>420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)</li> </ul>
LC50 Inhalation - Rat	> 5.14 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation))
LC50 Inhalation - Rat (Dust/Mist)	> 5.14 mg/l Source: ECHA

Copper (7440-50-8)	
LD50 oral rat	300 – 500 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: other:MAFF 4200 (1985)
LC50 Inhalation - Rat	> 5.11 mg/l air Animal: rat, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)

Nickel (7440-02-0)	
LD50 oral rat	> 9000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 10.2 mg/l (Exposure time: 1 h)

Molybdenum (7439-98-7)	
LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 5.84 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	> 3.92 mg/l Source: ECHA

Iron (7439-89-6)	
LD50 oral rat	98600 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 250 mg/m³ air (6 h, Rat, Male, Experimental value, Inhalation (dust))

## Material Safety Data Sheet

Chromium (7440-47-3)	
· · ·	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 420, Rat, Male / female, Read- across, Oral, 14 day(s))
LC50 Inhalation - Rat	> 5.41 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 5.41 mg/l Source: ECHA
Skin corrosion/irritation:	
Not classified	
Serious eye damage/irritation:	
Not classified	
Respiratory sensitization:	
Not classified	
Skin sensitization:	
May cause an allergic skin reaction.	
Carcinogenicity:	
Suspected of causing cancer.	
Nickel (7440-02-0)	
IARC group	2B - Possibly carcinogenic to humans
Chromium (7440-47-3)	
IARC group	3 - Not classifiable
Mutagenicity:	
Not classified	
Reproductive toxicity:	
Not classified	
STOT-single exposure:	
Not classified	
STOT-repeated exposure:	
Causes damage to organs through prolonged or repeat	ed exposure.
Nickel (7440-02-0)	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.004 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Molybdenum (7439-98-7)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	<ul> <li>&gt; 0.1 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)</li> </ul>
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Chromium (7440-47-3)	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	≥ 0.0044 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

### Aspiration hazard:

Not classified		
T-316L		
Viscosity, kinematic	Not applicable	
Silicon Metal (7440-21-3)		
Density	2.33 g/cm <sup>3</sup> Type: 'density' Temp.: 25 °C	
Viscosity, dynamic	Not applicable (solid)	
Manganese (7439-96-5)		
Density	7200 kg/m <sup>3</sup>	
Copper (7440-50-8)		
Density	0.47 g/ml Type: 'tap density' Temp.: 20 °C	
Nickel (7440-02-0)		
Viscosity, kinematic (calculated value) (40 °C)	Not applicable (solid)	
Density	8.9 g/cm³ (at 25 °C)	
Viscosity, kinematic	Not applicable (solid)	
Viscosity, dynamic	Not applicable (solid)	
Molybdenum (7439-98-7)		
Density	10.2 g/cm³ (at 20 °C)	
Iron (7439-89-6)		
Density	7.87 g/cm³ Type: 'density' Temp.: 20 °C	
Chromium (7440-47-3)		
Density	7.19 g/cm <sup>3</sup> (at 20 °C)	
	1	

: Harmful to aquatic life with long lasting effects.
: Not classified
: Harmful to aquatic life with long lasting effects.

Silicon Metal (7440-21-3)	
LC50 - Fish [1]	100 mg/l (Pisces)
EC50 72h - Algae [1]	250 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	250 mg/l (Equivalent or similar to OECD 201, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Weight of evidence)

# Material Safety Data Sheet

Manganese (7439-96-5)	
LC50 - Fish [1]	> 3.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 1.6 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	2.8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '8 d'
BCF - Fish [1]	81 (Pisces)
BCF - Other aquatic organisms [1]	300000 (Mollusca)
BCF - Other aquatic organisms [2]	125000 (Crustacea)

Copper (7440-50-8)	
LC50 - Fish [1]	0.0068 – 0.0156 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 - Fish [2]	< 0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 96h - Algae [1]	0.031 – 0.054 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 72h - Algae [1]	0.0426 – 0.0535 mg/l (Species: Pseudokirchneriella subcapitata [static])
Partition coefficient n-octanol/water (Log Pow)	-0.57 Source: EPISUITE

Nickel (7440-02-0)	
LC50 - Fish [1]	> 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
LC50 - Fish [2]	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 - Crustacea [1]	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 96h - Algae [1]	0.174 – 0.311 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 72h - Algae [1]	0.18 mg/l (Species: Pseudokirchneriella subcapitata)
BCF - Other aquatic organisms [1]	8 – 45 (≤ 4 week(s), Cambarus sp., Flow-through system, Fresh water, Experimental value, Fresh weight)

Molybdenum (7439-98-7)	
LC50 - Fish [1]	609.1 mg/l Source: EHCA
EC50 72h - Algae [1]	289.2 mg/l Source: ECHA
BCF - Fish [1]	260 – 500 (Tilapia rendalli)
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC Access on Jan 2006

Iron (7439-89-6)	
LC50 - Fish [1]	8.65 mg/l Source: ECHA
LC50 - Other aquatic organisms [1]	106.3 mg/l Source: ECHA
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	> 10000 mg/l Test organisms (species): Daphnia magna

# Material Safety Data Sheet

Iron (7439-89-6)		
EC50 72h - Algae [1]	18 mg/l Source: ECHA	
Chromium (7440-47-2)		
Chromium (7440-47-3)		
LC50 - Fish [1]	13.9 – 210 mg/l Source: GESTIS	
EC50 - Crustacea [1]	17.7 – 18.9 mg/l Source: ECHA	
EC50 72h - Algae [1]	0.1 – 17.8 mg/l Source: GESTIS	
BCF - Fish [1]	0.0048 (Pisces, Literature study, Dry weight)	
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC	
12.2. Persistence and degradability		
Silicon Metal (7440-21-3)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
Manganese (7439-96-5)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	
Copper (7440-50-8)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	
Nickel (7440-02-0)		
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
Molybdenum (7439-98-7)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

Iron (7439-89-6)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Chromium (7440-47-3)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

## 12.3. Bioaccumulative potential

# Silicon Metal (7440-21-3)

Bioaccumulative potential

Not bioaccumulative.

Manganese (7439-96-5)	
BCF - Fish [1]	81 (Pisces)
BCF - Other aquatic organisms [1]	300000 (Mollusca)
BCF - Other aquatic organisms [2]	125000 (Crustacea)
Bioaccumulative potential	No bioaccumulation data available.

Copper (7440-50-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.57 Source: EPISUITE
Bioaccumulative potential	Bioaccumulation: not applicable.

Nickel (7440-02-0)		
BCF - Other aquatic organisms [1]	$8-45~(\leq 4~\text{week(s)},~\text{Cambarus sp.},~\text{Flow-through system},~\text{Fresh water},~\text{Experimental value},~\text{Fresh weight})$	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	

Molybdenum (7439-98-7)		
BCF - Fish [1]	260 – 500 (Tilapia rendalli)	
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC Access on Jan 2006	
Bioaccumulative potential	No bioaccumulation data available.	

Iron (7439-89-6)	
Bioaccumulative potential	No bioaccumulation data available.

Chromium (7440-47-3)		
BCF - Fish [1]       0.0048 (Pisces, Literature study, Dry weight)		
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC	
Bioaccumulative potential	Not bioaccumulative.	

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

12.4. Mobility in soil			
Silicon Metal (7440-21-3)			
Ecology - soil	Highly mobile in soil.		
Manganese (7439-96-5)			
Ecology - soil	No (test)data on mobility of the substance available.		
Copper (7440-50-8)			
Partition coefficient n-octanol/water (Log Pow)	-0.57 Source: EPISUITE		
Ecology - soil	Adsorbs into the soil.		
Nickel (7440-02-0)			
Surface tension	Not applicable (solid)		
Ecology - soil	No (test)data on mobility of the substance available.		
Molybdenum (7439-98-7)			
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC Access on Jan 2006		
Ecology - soil	Adsorbs into the soil.		
Iron (7439-89-6)			
Surface tension	Not applicable (solid)		
Ecology - soil	Adsorbs into the soil.		
Chromium (7440-47-3)			
Surface tension	No data available (test not performed)		
Partition coefficient n-octanol/water (Log Pow)	0.23 Source: SRC		
Ecology - soil	No (test)data on mobility of the substance available.		
12.5. Other adverse effects			
Ozone	· Not classified		

 Ozone
 : Not classified

 Other adverse effects
 : No data available

## 13. Disposal considerations

## 13.1. Disposal method

Dispose of contents/container in accordance with licensed collector's sorting instructions.

13.2. Disposal precaution

No data available

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

UN RTDG	ADR	IMDG	ΙΑΤΑ
14.1. UN number	I		
Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Marine pollutant			
Not applicable	Not applicable	Not applicable	Not applicable

### 14.6. Special precautions for user

No data available

## 15. Regulatory information

15.1. Occupational Safety and Health Act		
Hazardous Substances Prohibited for Manufacturing Hazardous Substances Requiring Permission	Not applicable Not applicable	
Threshold Limit Values Chemicals	Applicable	7440-21-3: Silicon
		7439-96-5: Manganese&Inorganic compounds, as Mn
		7440-50-8: Copper
		7440-02-0: Nickel
		7439-98-7: Molybdenum
		7439-89-6: Iron salts (Soluble, as Fe)
		7440-47-3: Chromium
Hazardous Substances Below Permissible Level	Applicable	7439-96-5: Manganese and its inorganic compounds
		7440-02-0: Nickel and its insoluble inorganic compounds
Hazardous Substances Subject to Working	Applicable	7439-96-5: Manganese and its inorganic compounds
Environment Measurement		7440-50-8: Copper
		7440-02-0: Nickel and its inorganic compounds
		7440-47-3: Chromium and its inorganic compounds
Hazardous Substances Subject to Workers Requiring	Applicable	7439-96-5: Manganese and its inorganic compounds
Health Examination		7440-50-8: Copper
		7440-02-0: Nickel and its inorganic compounds
		7440-47-3: Chromium and its compounds
Hazardous Substances Subject to Control	Applicable	7439-96-5: Manganese and its inorganic compounds
		7440-50-8: Copper and its compounds
		7440-02-0: Nickel and its inorganic compounds
		7439-89-6: Iron and its compounds
		7440-47-3: Chromium and its compounds(except Chromium(VI) compounds)

## **15.2. Chemicals Control Act**

No data available

## 15.3. ACT ON REGISTRATION, EVALUATION, ETC. OF CHEMICALS (K-REACH)

#### No data available

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

15.4. Safety Control of Dangerous Substa	ances Act	
Safety Control of Dangerous Substances Act	Applicable	(Class 2 Combustible solid - category 5 Metal powder (Designated quantity: 500kg); Class 2 Combustible solid - category 4 Iron Powder (Designated quantity: 500kg))
	Applicable	<ul> <li>7440-21-3: Silicon powder</li> <li>(Class 2 Combustible solid - category 5 Metal powder (Designated quantity: 500kg))</li> <li>7439-96-5: Manganese powder</li> <li>(Class 2 Combustible solid - category 5 Metal powder (Designated quantity: 500kg))</li> <li>7439-98-7: Molybdenum powder</li> <li>(Class 2 Combustible solid - category 5 Metal powder (Designated quantity: 500kg))</li> <li>7439-98-7: Molybdenum powder</li> <li>(Class 2 Combustible solid - category 5 Metal powder (Designated quantity: 500kg))</li> <li>7439-89-6: Iron powder</li> <li>(Class 2 Combustible solid - category 4 Iron Powder (Designated quantity: 500kg))</li> <li>7440-47-3: Chromium powder</li> <li>(Class 2 Combustible solid - category 5 Metal powder (Designated quantity: 500kg))</li> </ul>

15.5. Wastes Control Act			
Hazardous Substances in Designated wastes	Applicable		

Types of wastes

No data available

Not applicable

Not applicable

### **15.6. Other Domestic and International Regulatory Information**

#### **Domestic**

Persistent Organic Pollutants(POPs) Control Act Ozone Depleting Substances(ODS)

International

### **EU Regulatory Information**

EU Candidate list (SVHC) EU authorization list (REACH Annex XIV) EU restriction list (REACH Annex XVII)

#### **US Regulatory Information**

CERCLA Section 103 (40CFR302.4) EPCRA Section 302 (40CFR355.30) EPCRA Section 304 (40CFR355.40) EPCRA Section 313 (40CFR372.65)

#### International agreements

No data available

Contains no substance on the REACH candidate list Contains no REACH Annex XIV substances Not applicable

Contains listed substances Not applicable Not applicable Contains listed substances

## Material Safety Data Sheet

In Accordance with MOEL Public notice No 2020-130

16. Other information	
16.1. Data sources: 16.2. Issue date:	REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006, Supplier's safety documents, No data available, This MSDS is prepared based on Article 41 of the Occupational Safety and Healt Act and Notice No.2016-19 of the Ministry of Employment and Labor (based on the availability of material safety and health data), taking into account the status of regulations related to Korea, ECHA (European Chemicals Agency), Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013, This MSDS is prepared based on KOSHA, NITE, ESIS, NLM, SIDS, IPCS, NCIS, etc, This safety data sheet was compiled with data and information from the following sources : RTECS, ECOSAR, HSDB, SIDS SIAP, ChemWATCH, CESAR, Chemical DB. 6/5/2011
16.3. Revision number and date:	4.0, 16/02/2023
16.4. Other information:	No data available

requirements only. It should not therefore be construed as guaranteeing any specific property of the product.